

SUPERBIT TAPE

Self-adhesive asphalt tape for waterproofing and sealing.

Description

High quality, elastic self-adhesive tape, from distilled asphalt modified with elastomeric polymers and special additives. Reinforced with glass fibre tissue and protected on the upper side by aluminium foil. Very easy to install with excellent adhesion, offers complete watertightness, good resistance to acids and alkalis, excellent protection from UV and reduces the flame spread in case of fire. Ideal for all building materials in sealing joints in gutters, chimneys, tiles.

Applications

Ideal for permanent sealing of joints in gutters, chimneys, tiles etc. Can be used in roof and basement repairs, repair of joints and cracks, to seal roof windows, dormer windows and chimneys, parts in boats, containers and caravans, as well as to protect and seal drainage and pipes.

Technical features

Roll length: 10 m

Roll width: 15 cm

Thickness: 1,4 mm

Temperature resistance: - 20 °C to + 90 °C

Tensile strength:

Longitudinal: 400 N / 5 cm

Transversal: 300 N / 5 cm

Elongation of the compound: > 1500

Elongation at max load:

Longitudinal: 2%

Transversal: 2%

Tear strength (nail shank):

Longitudinal: 80 N

Transversal: 100 N

Substrate surface preparation

Ensure clean, dry surfaces, free from any shrinking tendencies. Remove any loose material or detached fragments, dust, grease etc.

Instructions for use

1. Cut the sealing tape to the required length.
2. Peel off the siliconized film.
3. Apply the tape and ensure that there is a tape overlap of at least 5 cm



Storage

Store in a cool and dry location, away from direct contact with the sunlight. Use within 24 months from the production date.

Consumption

When calculating consumption allow for a tape overlap of at least 5 cm.

Packaging

Rolls of 10 m

Precautions and safety

This product is not hazardous as defined in the Hazardous Substances Code. Can be disposed as building waste.

Notes

Technical data, properties, recommendations and information on BAUER products are supplied in good faith. They are based on the company's research and experience, provided that they are stored and applied under normal conditions. Given that in each case of application, the use of the materials and the conditions of the project as well as the overall environment, cannot be controlled by the company, the sole responsibility for the result lies with the end user of the product. No liability under any legal relationship can be established against the company, based on the information listed within this document. The present edition of this Technical Data Sheet automatically cancels any previous editions. The end user of the products should always refer to the latest Technical Data Sheet version.

Other information

BAUER BUILDING TECHNOLOGIES

Megara Industrial Estate, Attica

Tel: +30 210 5744222

Fax: +30210 5740777

Email: info@netbauer.com

[http:// www.netbauer.com](http://www.netbauer.com)

Frankfurt, Reg. No 312310 QM

Qualitätsmanagementsystem

Zertifiziert nach DIN EN ISO 9001

